





Plastic Tube and Hose Fittings CONTINUED


SWIVEL ADAPTERS AND NUTS



		Part No.	
		Nylon	Black HDPE
Nuts–Swivel			
			FPT
			Hose ID
SAN 4			1/4
SAN 4W			1/4 Wing
SAN 6	Not available		3/8
SAN 8			1/2
SAN G			GHT
Adapters–Swivel			
			Fits nut size
SA 4		SAN 4 or 4W	1/4
SA 6		SAN 6	3/8
SA 8		SAN 8	1/2
SA 8-4		SAN 8	1/4
	Not available		
SAG 4			1/4
SAG 6		SAN G	3/8
SAG 8			1/2
SAG 12			3/4

Minimum order 50.


CONNECTORS–BARBED HOSE MENDERS



		Hose ID	Hose ID
C 22	C 22 PE	1/8	1/8
C 33	C 33 PE	3/16	3/16
C 44	C 44 PE	1/4	1/4
C 55	C 55 PE	5/16	5/16
C 66	C 66 PE	3/8	3/8
C 88	C 88 PE	1/2	1/2
C 1010	C 1010 PE	5/8	5/8
C 1212	C 1212 PE	3/4	3/4
C 1616	C 1616 PE	1	1
C 114	—	1-1/4	1-1/4
C 112	—	1-1/2	1-1/2

Minimum order 50.

CONNECTORS–REDUCING



		Tube ID	Tube ID
C 42	C 42 PE		1/8
C 43	C 43 PE	1/4	3/16
C 64	C 64 PE	3/8	1/4
C 84	C 84 PE		1/4
C 86	C 86 PE	1/2	3/8
C 106	C 106 PE		3/8
C 108	C 108 PE	5/8	1/2

Minimum order 50.

NOTES:

FPT – Female taper pipe thread
GHT – Garden hose thread


Temperature Ratings

HDPE: -55° to +90°C
Nylon: -40° to +100°C



Miniature Nylon Tube Fittings CONTINUED


CONNECTORS—BARBED



Part No.	Tube ID
MIC 00	1/16
MIC 11	3/32
MIC 22	1/8
MIC 33	3/16
MIC 44	1/4
MIC 66	3/8
MIC 88	1/2

Minimum order 50.


BARBED CONNECTORS—REDUCING



Part No.	Tube ID
MIC 01	3/32 to 1/16
MIC 02	1/8 to 1/16
MIC 12	1/8 to 3/32
MIC 32	3/16 to 1/8
MIC 453	1/4 to 5/32
MIC 43	1/4 to 3/16
MIC 62	3/8 to 1/8
MIC 64	3/8 to 1/4

Minimum order 50.


THREAD REDUCERS



Part No.	Thread
MIR 21	1/8 MPT to 10/32 UNF
MIR 225	1/8 MPT to 1/4-28 UNF
MIR 41	1/4 MPT to 10/32 UNF
MIR 425	1/4 MPT to 1/4-28 UNF
MIR 42	1/4 MPT to 1/8-27 FPT

Minimum order 50.


NIPPLE



Part No.	Thread
MIN 11	10/32 UNF
MIN 22	1/8 MPT
MIN 44	1/4 MPT

Minimum order 50.

PLUGS



Part No.	Thread
MIP 1	10/32 UNF
MIP 2	1/8 MPT
MIP 4	1/4 FPT

Minimum order 50.

NOTES:


MPT—Male taper pipe thread

Temperature Ratings

Nylon: -40° to +100°C

Polypropylene: -20° to +100°C

LOCKING SLEEVES



Locking sleeves enable barbed fittings to be used at up to 100% of the rated burst pressure of the flexible plastic tubing. To use, simply slide appropriate

sleeve over suggested OD tubing, insert miniature barbed fitting into tubing, slide sleeve back over barb. Soft tubing locks onto the self-sealing barb.

Part No.	Tube OD	SD	T	ID
LS 125	1/8	.310	.245	.147
LS 156	5/32	.375	.281	.176
LS 187	3/16	.400	.300	.215
LS 250	1/4	.435	.315	.260
LS 375	3/8	.625	.375	.425

Minimum order 1000.