




# Miniature Nylon Tube Fittings CONTINUED


## CONNECTORS—BARBED



Part No.	Tube ID
MIC 00	1/16
MIC 11	3/32
MIC 22	1/8
MIC 33	3/16
MIC 44	1/4
MIC 66	3/8
MIC 88	1/2

Minimum order 50.


## BARBED CONNECTORS—REDUCING



Part No.	Tube ID
MIC 01	3/32 to 1/16
MIC 02	1/8 to 1/16
MIC 12	1/8 to 3/32
MIC 32	3/16 to 1/8
MIC 453	1/4 to 5/32
MIC 43	1/4 to 3/16
MIC 62	3/8 to 1/8
MIC 64	3/8 to 1/4

Minimum order 50.


## THREAD REDUCERS



Part No.	Thread
MIR 21	1/8 MPT to 10/32 UNF
MIR 225	1/8 MPT to 1/4-28 UNF
MIR 41	1/4 MPT to 10/32 UNF
MIR 425	1/4 MPT to 1/4-28 UNF
MIR 42	1/4 MPT to 1/8-27 FPT

Minimum order 50.


## NIPPLE



Part No.	Thread
MIN 11	10/32 UNF
MIN 22	1/8 MPT
MIN 44	1/4 MPT

Minimum order 50.

## PLUGS



Part No.	Thread
MIP 1	10/32 UNF
MIP 2	1/8 MPT
MIP 4	1/4 FPT

Minimum order 50.

### NOTES:


MPT—Male taper pipe thread

### Temperature Ratings

Nylon: -40° to +100°C

Polypropylene: -20° to +100°C

## LOCKING SLEEVES



Locking sleeves enable barbed fittings to be used at up to 100% of the rated burst pressure of the flexible plastic tubing. To use, simply slide appropriate

sleeve over suggested OD tubing, insert miniature barbed fitting into tubing, slide sleeve back over barb. Soft tubing locks onto the self-sealing barb.

Part No.	Tube OD	SD	T	ID
LS 125	1/8	.310	.245	.147
LS 156	5/32	.375	.281	.176
LS 187	3/16	.400	.300	.215
LS 250	1/4	.435	.315	.260
LS 375	3/8	.625	.375	.425

Minimum order 1000.