





Nylon Flat Washers CONTINUED

RETAINING



Similar to our standard flat washer, but with a specially configured inside diameter designed to grip the outside of the screw shank. The washer slides on the screw easily, but is retained on the screw.

For use in applications requiring pre-assembly of the screw and washer to reduce final assembly cost.

Other sizes may be tooled on request.

Part No.	ID	Retaining dia.		OD	T
		R			
FWR 2-032	.078	.115		13/64	.031
FWR 2-062	.078	.115		13/64	.062
FWR 4-032	.102	.156		17/64	.031
FWR 4-062	.102	.156		17/64	.062
FWR 6-032	.128	.198		21/64	.031
FWR 6-062	.128	.198		21/64	.062
FWR 8-032	.152	.235		25/64	.031
FWR 8-062	.152	.235		25/64	.062
FWR 10-032	.177	.277		29/64	.031
FWR 10-062	.177	.277		29/64	.062
FWR 250-032	.234	.375		19/32	.031
FWR 250-062	.234	.375		19/32	.062
FWR 312-032	.292	.470		47/64	.031
FWR 312-062	.292	.470		47/64	.062
FWR 375-032	.350	.564		57/64	.031
FWR 375-062	.350	.564		57/64	.062
FWR 437-032	.410	.570		1-1/32	.031
FWR 437-062	.410	.570		1-1/32	.062
FWR 500-032	.468	.690		1-1/8	.031
FWR 500-062	.468	.690		1-1/8	.062

Minimum order 1000.