

Hose Clamps

HOSERS (ACETAL TUBE AND HOSE CLAMPS)



A non-metallic clamp that will not rust, is non-conducting, not corroded by sea water and is stable in a wide variety of chemical salts, bases, alcohols, oil, grease, gasoline, etc. Often used in place of stainless clamps.

Can be applied by quick ratchet closure, even after hose is in place. A lateral effort disengages the clamp. A stand and a pneumatic closing tool are also available.

Stocked in acetal. Black heat- and UV-stabilized, glass-filled nylon (for outdoor or under the hood applications) also available at an additional charge.

Part No.	Diameter Range	Width
HO 1	.228 -.256	.148
HO 1.5	.307 -.342	.146
HO 2	.351 -.394	.231
HO 4	.404 -.452	.233
HO 6	.449 -.511	.233
HO 7	.453 -.546	.253
HO 8	.513 -.586	.231
HO 10	.569 -.650	.233
HO 12	.616 -.707	.234
HO 14	.702 -.801	.233
HO 16	.746 -.848	.232
HO 18	.779 -.899	.237
HO 19	.859 -.989	.233
HO 22	.928 - 1.072	.234
HO 24	.985 - 1.135	.292
HO 28	1.123 - 1.296	.288
HO 32	1.218 - 1.405	.287
HO 34	1.338 - 1.566	.292
HO 36	1.472 - 1.724	.287
HO 38	1.594 - 1.862	.291
HO 42	1.729 - 2.021	.288
HO 50	1.999 - 2.277	.291
HO 60	2.259 - 2.582	.290
HO 70	2.536 - 2.881	.288
HO 76	2.839 - 3.206	.387
HO 80	3.144 - 3.562	.388
HO 90	3.506 - 3.922	.385
HO 100	3.871 - 4.395	.394

Minimum order 100.

NYLON HOSE MATES™



Cords has a full line of nylon hose clamps. They are quick, easy to install and tighten instantly with hand pliers. These lightweight clamps resist salt water corrosion, weak acids, grease and common solvents. Hose Mates™ can be removed without cutting, so they are reusable – both recyclable and cost-effective!

Hose Mates™ are available in seventeen popular sizes, from a minimum diameter of 1/4" up to a maximum diameter of 2-3/8". Cords stocks them in black and white nylon, and they are also available in black glass-filled nylon.